

Posts · Fencing · Gates · Tools



www**.whitesrural.**com.au



Posts · Fencing · Gates · Tools

Australian family owned, down to earth, no nonsense

Whites Group has been listening and responding to the needs of Australian farmers and fencing contractors for over 40 years.
Continuously developing better fencing ideas proven to work on the farm, Whites Group has pioneered a number of original ideas like Stockpost Ute Pack, designed to get the job done with a minimum of fuss.

Australian owned and operated, Whites Group is a family business with its roots strongly embedded in steel, wire and fencing products since 1977. Today, Australian manufacturing is at the heart of Whites Rural's wire range made in Albury NSW, signifying a deeper, long-term commitment to the needs of rural Australia.





www.whitesrural.com.au

FARM FENCING Rural Catalogue





STOCKPOST the mark of a good post

| Stockpost [®] | 4 |
|--|---|
| Stockpost [®] Ute Pack [®] | 5 |
| Droppers | 5 |
| Stockpost [®] XL | 6 |
| Stockpost [®] End Assembly | 7 |
| Stockpost [®] Anti-Sink Plate | 7 |
| | |

Belle and a Bill of a Bill

FENCING

| Fence Wire | 8 |
|---|-------|
| Barbed Wire | 9 |
| Horse Sight Fence Wire | 9 |
| Stiff Knot [®] Prefabricated Fencing | 10-11 |
| Stiff Stay [®] Prefabricated Fencing | 12-14 |
| Hinged Joint | 15 |
| Heavy Netting | 16 |
| Farm Mesh | 17 |
| Welded Mesh | 18 |
| Horticulture | 19 |
| | |

GATES & FITTINGS

| Farm Gates | 20-21 |
|------------------------------|-------|
| Blue Label Farm Gates | 22 |
| XHD & Stockyard Farm Gates | 23 |
| Specialty Farm Gates | 24 |
| Ballimore & Feral Farm Gates | 25 |
| Gate Fittings | 26-27 |

TOOLS

| Drivers, Lifters & Wire Spinners | 28 |
|----------------------------------|-------|
| Strainers | 29 |
| Stapling | 30-31 |
| Fastening | 32 |
| MaxTensor® | 33 |
| Accessories | 34 |
| Farm Pak [™] Tie Wires | 34 |













| Code | Product | Size (ft) | Sling Qty | Weight (each) | Coating |
|-------|---|--------------|--------------|------------------|------------|
| STOCK | POST [®] - BLACK BITUMINO | US | | | |
| 10804 | 135cm STOCKPOST | 4'6" | 400 | 2.6kg | Black |
| 10807 | 150cm STOCKPOST | 5' | 400 | 2.8kg | Black |
| 10805 | 165cm STOCKPOST | 5'6" | 400 | 3.1kg | Black |
| 10806 | 180cm STOCKPOST | 6' | 400 | 3.4kg | Black |
| 10809 | 210cm STOCKPOST | 7' | 200 | 4.0kg | Black |
| 10808 | 240cm STOCKPOST | 8' | 200 | 4.6kg | Black |
| STOCK | POST [®] - HOT-DIPPED GAL ^V | VANISED | | | |
| 10814 | 135cm STOCKPOST | 4'6" | 200 | 2.6kg | Galvanised |
| 10817 | 150cm STOCKPOST | 5' | 200 | 2.8kg | Galvanised |
| 10815 | 165cm STOCKPOST | 5'6" | 200 | 3.1kg | Galvanised |
| 10816 | 180cm STOCKPOST | 6' | 200 | 3.4kg | Galvanised |
| 10819 | 210cm STOCKPOST | 7' | 200 | 4.0kg | Galvanised |
| 10818 | 240cm STOCKPOST | 8' | 200 | 4.6kg | Galvanised |



STOCKPOST[®]

Trusted, tried & true.

Consistently rolled from specially produced high grade steel, Stockpost is a premium fence post – strong and reliable.

- High strength, high consistency
- Coatings that withstand the test of time
- Innovative ground mark V
- Hole alignment that's straight up V
- Easy to drive

Stockpost is available in black bituminous dipped coating, providing a tough outer barrier, or hot-dipped galvanised to meet the Australian Standards for optimum protection.

Featuring consistent ground marks and centre marks for accurate height positioning; precision hole alignment & spacing for a uniform fence from the first to the last post; and uniformly cut end-points to drive in straight and easy.

Australian Innovation • Engineered for Consistency • Coatings that Last

| Hole S | pacing | | | | |
|--|--|--|--|---|--|
| 135cm | 150cm | 165cm | 180cm | 210cm | 240cm |
| 135cm 2.5cm 1.1cm 1. | 150cm 2.5cm 1.13cm 1.0cm 1 | 165cm 2.5cm 13cm 10cm | 180cm 2.5cm 1.13cm 1.0cm 1 | 210cm 2.5cm 6.5cm 10cm 10cm 10cm 6cm 6cm 7.5cm | 240cm 2.5cm 6.5cm 10cm 10cm 10cm 10cm 10cm 6cm 6cm 7.5cm 7.5cm 9.5cm 9.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm 7.5cm |





STOCKPOST[®] UTE PACK[®]

Australian designed Ute Pack - Stockpost quality & features in a contractor pack.

200 Stockposts in a secure steel cradle... and no tie wires!



Effortless Handling Packed as singles. No bundle ties.



Easy Load Pack Front-end loader and ute friendly.



Fast & Efficient Get it onto the ute and into the ground.



Refastenable Pack Use some or all, posts stay secure.



Australian Design Designed & patented in Australia, for Australian farmers.





| Code | Product | Size (ft) | Sling Qty | Weight (each) | Coating |
|--------|--|--------------|--------------|------------------|---------|
| STOCKF | POST [®] - BLACK BITUMINOUS | | | | |
| 10801 | 165cm STOCKPOST - UTE PACK | 5'6" | 200 | 3.1kg | Black |
| 10802 | 180cm STOCKPOST - UTE PACK | 6' | 200 | 3.4kg | Black |
| 10803 | 225cm STOCKPOST - UTE PACK | 7'6" | 200 | 4.3kg | Black |
| STOCKF | OST [®] - HOT DIPPED GALVANISED | | | | |
| 10811 | 165cm STOCKPOST - UTE PACK | 5'6" | 200 | 3.1kg | Galv |
| 10812 | 180cm STOCKPOST - UTE PACK | 6' | 200 | 3.4kg | Galv |
| 10810 | 225cm STOCKPOST - UTE PACK | 7'6" | 200 | 4.3kg | Galv |



| Product | Qty | (each) | Coating |
|---------------------|--|---|--|
| ENCE DROPPERS | | | |
| 63.5cm Droppers | 25 | 6kg | Hot Dip Galvanised |
| 81.5cm Droppers | 25 | 9.4kg | Hot Dip Galvanised |
| 94cm Droppers | 25 | 10.6kg | Hot Dip Galvanised |
| 107cm Droppers | 25 | 12.2kg | Hot Dip Galvanised |
| 117cm Droppers | 25 | 13.3kg | Hot Dip Galvanised |
| Dropper Clips 500gm | - | - | - |
| | ENCE DROPPERS 63.5cm Droppers 81.5cm Droppers 94cm Droppers 107cm Droppers 117cm Droppers | ProductQtyFENCE DROPPERS63.5cm Droppers2581.5cm Droppers94cm Droppers25107cm Droppers25117cm Droppers25 | Product Qty (each) ENCE DROPPERS 63.5cm Droppers 25 6kg 81.5cm Droppers 25 9.4kg 94cm Droppers 25 10.6kg 107cm Droppers 25 12.2kg 117cm Droppers 25 13.3kg |

DROPPERS

Whites Rural Fence Droppers are manufactured from high grade steel and heavily galvanised to ensure long life. Use with barbed wire or plain wire.

- Manufactured from high tensile steel
- Heavily galvanised for long life
- Pack of 25 includes tool and clips







STOCKPOST[®] XL

Meet Stockpost's BIG brother.

Stockpost XL is hot rolled from the same quality raw material as Stockpost, so you know it's good.

SMARTER

3 equal fins for all around stability and more holes per post (ideal for feral fencing). A great alternative to timber posts.

FASTER

Packed in a faster fencing Ute Pack sling for easy access, easy handling. 4:1 ratio – 200 Stockposts plus 50 Stockpost **XL**s provides a typical fencing ratio.

STRONGER

Hot rolled from the same quality raw material as Stockpost, independently NATA tested.





Hole Spacing





STOCKPOST X

STOCKPOSTX

| Code | Product | Size (ft) | Sling Qty | Weight (each) | Coating |
|-------|--------------------------------------|--------------|--------------|------------------|------------|
| STOCK | POST [®] - BLACK BITUMINOU | S | | | |
| 10846 | 180cm STOCKPOST XL | 6' | 50 | 6.3kg | Black |
| 10849 | 210cm STOCKPOST XL | 7' | 50 | 7.4kg | Black |
| 10848 | 240cm STOCKPOST XL | 8' | 50 | 8.4kg | Black |
| STOCK | POST [®] - HOT-DIPPED GALVA | ANISED | | | |
| 10856 | 180cm STOCKPOST XL | 6' | 50 | 6.3kg | Galvanised |
| 10859 | 210cm STOCKPOST XL | 7' | 50 | 7.4kg | Galvanised |
| 10858 | 240cm STOCKPOST XL | 8' | 50 | 8.4kg | Galvanised |
| | | | | | |





STOCKPOST[®] END ASSEMBLY

A fully hot-dipped galvanised end assembly system made with Stockpost quality, for high performance without the high price tag.

Featuring a heavy duty square steel Anchor Post with unique shark tooth points that cleverly cut through soil to avoid compaction for effortless driving. Each Anchor Post includes a steel cap and the Stockpost ground mark for easy fence line up at ground level.

Time saving & easy installation Fully hot-dipped galvanised Heavy duty registered design

The Stay Assembly Kit includes a 3m brace pipe with specially designed brace cap for ease of installation; a heavy duty fireproof base plate; and a notched threaded rod for easy tensioning.

The Stockpost End Assembly range also includes gate fittings and additional brace caps for 2, 3, and 4-way configurations.





base plate

fully hot-dipped "shark tooth' registered design galvanised





pre-drilled holes & heavy duty square post multiple configurations brace cap



clever edges to avoid compaction

innovative

ground mark

STOCKPOST[®] ANTI-SINK PLATE

Stabilise steel fence posts in soft or loose soils. The surface area of the wide base guards against sinking and limits movement. Simply attach at ground level using the steel locking pin. Easily retro-fitted to existing fences.

- High strength, galvanised steel
- Large 15cm base, greater support
- Suits Stockpost and Stockpost XL and most other steel "Y" posts



HDG 50NB pipe - 3m with Brace cap

2.1m HDG Anchor Post 90x90mm profile 3.75mm wall

> Innovative ground mark

HDG Steel cap

HDG M12 threaded rod supplied with fittings - 3.25m

HDG Fireproof Base Plate - 4mm

'Shark tooth' end point for easy driving

Multiple Configurations Possible

ground-breaking technology

| Code STOCK | Product POST [®] - END ASSEMBLY SYSTEM | Pack Qty | Weight (each) |
|---------------|--|-------------|------------------|
| 10870 | STOCKPOST Anchor Post 2.1m | 5 | 22.5kg |
| 10875 | STOCKPOST Stay Assembly 3m | 5 | 17.1kg |
| STOCK | POST [®] - END ASSEMBLY ACCESSORIES | | |
| 10876 | STOCKPOST Brace Cap with Spike | 10 | 0.5kg |
| 13855 | End Assembly Gate Fitting Top Strap & Gudgeon | 5 | 2.4kg |
| 13856 | End Assembly Gate Fitting Drop Latch & Eyelet | 5 | 1kg |





| Code | Product | Pack Qty | Weight (each) |
|-------|-------------------------------------|-------------|------------------|
| STOCK | POST [®] - ANTI-SINK PLATE | | |
| 12218 | STOCKPOST Anti-Sink Plate | 20 | 0.2kg |







Australian Standards

| Code | Wire | Tensile Strength | Coil Length | Coil Weight | Sling Qty | Galv. Coating | Rec. Tension Breaking Strain | |
|-------------------------------|----------|---------------------|----------------|----------------|--------------|------------------|---------------------------------|--|
| HEAVILY GALVANISED FENCE WIRE | | | | | | | | |
| 10014 | 2.50mm | Medium | 1500m | 58kg | 10 | Heavy | 1.3kn, 3.7kn | |
| 10015 | 2.50mm | High | 1500m | 58kg | 10 | Heavy | 1.8kn, 5.4kn | |
| 10016 | 2.80mm | High | 1000m | 48kg | 10 | Heavy | 2.0kn, 6.8kn | |
| 10017 | 3.15mm | Soft | 750m | 46kg | 10 | Heavy | 1.2kn, 3.0kn | |
| 10018 | 4.00mm | Soft | 500m | 50kg | 10 | Heavy | 1.8kn, 4.8kn | |
| STANDA | ARD GALV | ANISED FE | INCE WIR | E | | | | |
| 10161 | 4.00mm | Soft | 500m | 49kg | 10 | Standard | 1.8kn, 4.8kn | |
| 10163 | 3.15mm | Soft | 750m | 46kg | 10 | Standard | 1.2kn, 3.0kn | |
| 10170 | 2.50mm | Medium | 1500m | 58kg | 10 | Standard | 1.3kn, 3.7kn | |
| 10171 | 2.50mm | High | 1500m | 58kg | 10 | Standard | 1.8kn, 5.4kn | |
| STANDA | RD GALV | ANISED TI | E WIRE | | | | | |
| 10164 | 2.50mm | Soft | 1300m | 50kg | 10 | Standard | 1.3kn, 3.7kn | |
| 10165 | 2.00mm | Soft | 2000m | 50kg | 10 | Standard | - | |
| 10166 | 1.57mm | Soft | 3200m | 50kg | 10 | Standard | - | |



| Code HANDY | Wire FENCE [™] | Tensile Strength | Coil Length | Coil Weight | Sling Qty | Galv. Coating | Rec. Tension Breaking Strain |
|---------------|----------------------------|---------------------|----------------|----------------|--------------|------------------|---------------------------------|
| 10011 | 2.50mm | Medium | 300m | 11.6kg | 10 | Standard | 1.3kn, 3.7kn |
| 10012 | 3.00mm | Soft | 250m | 13.9kg | 10 | Standard | 1.2kn, 3.0kn |



RURAL FENCE WIRE

Whites Rural Heavily Galvanised and Standard Galvanised Rural Fence Wire are made to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Heavily Galvanised

Heavily Galvanised to last up to four times longer than standard galvanising.

Standard Galvanised

Standard Galvanised Fence Wire and Tie Wire are economical fencing options, with a quality you can trust.

- Soft easy to handle and tie
- Medium Tensile ideal with prefab fencing
- High Tensile suited to longer strains

The wire is recoiled on new machines to provide smooth & tangle free delivery off the wire spinner, saving contractors and farmers expensive down time. Produced on the latest, highest tolerance recoilers to electronically deliver full and accurate details for each coil of wire.



HANDYFENCE

Whites Rural Handyfence coils, a great option for smaller fencing runs or for quick and easy repairs to fences.





BARBED WIRE

Whites Rural Barbed Wire is made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Produced on new machines which are the latest and highest tolerance barbed wire machines available today, the barbs are tightly twisted to prevent them from slipping out of position. All barbed wires are supplied rolled on hardwood timber reels.

High Tensile Barbed Wire

Reverse twist style for optimum strength & tensioning.

IOWA Barbed Wire

IOWA continuous-twist style.



HORSE SIGHT FENCE WIRE

Used as a top wire on horse fencing to increase visibility and prevent injury to horses.

- White PVC coating improves visibility
- Reduces damage to fences and injury to horses
- UV stabilised PVC coating





| Code | Wire | Tensile Strength | Coil Length | Coil Weight | Pallet Qty | Galv. Coating | Rec. Tension Breaking Strain |
|----------------|-----------|---------------------|----------------|----------------|---------------|------------------|---------------------------------|
| HIGH TI | ENSILE BA | RBED WIF | RE | | | | |
| 10100 | 2.00mm | High | 500m | 37kg | 36 | Heavy | 1.6kn, 5.0kn |
| 10101 | 1.80mm | High | 500m | 28kg | 36 | Heavy | 1.3kn, 4.0kn |
| 10102 | 1.57mm | High | 500m | 24kg | 48 | Heavy | 1.3kn, 3.0kn |
| IOWA B | ARBED WI | RE | | | | | |
| 10150 | 2.50mm | Soft | 400m | 45kg | 27 | Standard | 1.3kn, 3.0kn |
| 10151 | 2.50mm | Soft | 400m | 45kg | 27 | Heavy | 1.3kn, 3.0kn |



*5.2mm total diameter including PVC coating

| Code | Wire | Tensile Strength | Coil Length | Coil Weight | - 3 | Galv. Coating | Rec. Tension Breaking Strain | | | |
|-------|------------------------|---------------------|----------------|----------------|-----|------------------|---------------------------------|--|--|--|
| HORSE | HORSE SIGHT FENCE WIRE | | | | | | | | | |
| 10169 | 5.2mm* | Soft | 400m | 43kg | 5 | Standard | 2.0kn, 6.0kn | | | |









| Heavily Galv. Code (Weight) STIFF KNOT° FARM F | Product ENCING | Roll Length | Tensile Strength | Pallet Qty |
|--|-------------------|-------------|---------------------|---------------|
| A0348 (70kg) | 5/70/30 | 200m | High | 9 |
| 10331 (80kg) | 6/70/30 | 200m | High | 9 |
| A0335 (162kg) | 6/70/30 | 400m | High | 4 |
| 10332 (85kg) | 6/90/30 | 200m | High | 9 |
| A0336 (171kg) | 6/90/30 | 400m | High | 4 |
| A0382 (73kg) | 6/90/45 | 200m | High | 9 |
| 10333 (96kg) | 7/90/30 | 200m | High | 9 |
| A0337 (193kg) | 7/90/30 | 400m | High | 4 |
| A0384 (83kg) | 7/90/45 | 200m | High | 9 |
| 10334 (106kg) | 8/90/30 | 200m | High | 9 |
| A0339 (213kg) | 8/90/30 | 400m | High | 4 |

FENCING STIFF KNOT Prefabricated Fencing

STIFF KNOT[®]

Stiff Knot prefabricated fencing is made in Australia on the fixed knot machine. The name Stiff Knot is trademarked to Whites and made exclusively by Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Stiff Knot is a large fixed knot that rigidly locks line wires to one-piece vertical pickets.

Considered the strongest knot available, it provides maximum strength by absorbing impact and spreading the load.

No exposed ends which can snag livestock. Available with optional hinged apron.



FARM FENCING

Manufactured to Australian Standards AS 2423-2002 and zinc coated to AS/NZS 4534-2006. Made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Heavily Galvanised Stiff Knot features high tensile 2.8mm line wires at top and bottom; 2.5mm high tensile line wires with graduated spacings; 2.5mm vertical stay wires.

Spacing Chart





STIFF KNOT Exclusion Fencing

EXCLUSION FENCING

Narrow 15cm picket spacings for smaller animals made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Stiff Knot exclusion fencing features:

Premium Coating & Wire Grade

- Heavily Galvanised
- 2.8mm high tensile top and bottom line wires
- 2.5mm high tensile line wires and 2.5mm vertical stay wires

Continuous Vertical Pickets

- Stiff Knot features continuous vertical pickets which are locked into place to resist sagging & buckling
- Compared to hinged joint fencing, they also provide a better fence over undulating land following the contour of the ground

Optional Pre-attached Hinged Apron

- Pre-attached to the bottom line wire with a hinged joint, the apron is a 300mm section of fence laid on the ground, restricting penetration or digging under the fence
- Exclusion fencing without hinged aprons require the fencing to be forced onto the ground, placing unnecessary stress on your fence posts
- The hinged version is both faster to install and easier on the fence, giving it a longer service life
- Also referred to as a hinged footer

Pre-Stripped Roll

- Stiff Knot has the first two pickets and the last two pickets removed from every roll
- A convenient aid for faster installation around end assemblies - no need to strip picket wires

Tension Crimps

- Stiff Knot line wires include tension crimps that provide a quick visual when judging the correct tension
- When the crimp is half flattened, the tension is generally sufficient; when no crimp can be seen, then the tension in the wire is too high and needs to be reduced





| Heavily Galv. Code (Weight) | Product | Hinged Apron | Roll Length | Tensile Strength | Pallet Qty |
|--------------------------------|-------------|-----------------|-------------|---------------------|---------------|
| STIFF KNOT [®] EXC | LUSION FENC | ING | | | |
| 10338 (74kg) | 8/90/15 | | 100m | High | 9 |
| A0367 (101kg) | 8/90/15 | 30cm 3-line | 100m | High | 9 |
| A0341 (144kg) | 8/90/15 | | 200m | High | 4 |
| A0368 (202kg) | 8/90/15 | 30cm 3-line | 200m | High | 4 |
| A0389 (93kg) | 11/90/15 | | 100m | High | 9 |
| A0385 (127kg) | 11/90/15 | 30cm 4-line | 100m | High | 9 |
| A0351 (106kg) | 13/90/15 | | 100m | High | 9 |
| A0355 (133kg) | 13/90/15 | 30cm 3-line | 100m | High | 9 |
| 10339 (80kg) | 8/115/15 | | 100m | High | 9 |
| A0370 (107kg) | 8/115/15 | 30cm 3-line | 100m | High | 9 |
| A0340 (161kg) | 8/115/15 | | 200m | High | 4 |
| A0371 (215kg) | 8/115/15 | 30cm 3-line | 200m | High | 4 |
| A0372 (254kg) | 11/115/15 | 30cm 3-line | 200m | High | 4 |
| 10359 (113kg) | 13/115/15 | | 100m | High | 9 |
| A0373 (140kg) | 13/115/15 | 30cm 3-line | 100m | High | 9 |
| A0358 (266kg) | 13/115/15 | | 200m | High | 4 |
| A0374 (280kg) | 13/115/15 | 30cm 3-line | 200m | High | 4 |
| A0380 (118kg) | 13/137/15 | | 100m | High | 9 |
| A0378 (145kg) | 13/137/15 | 30cm 3-line | 100m | High | 9 |
| A0383 (237kg) | 13/137/15 | | 200m | High | 4 |
| A0379 (291kg) | 13/137/15 | 30cm 3-line | 200m | High | 4 |
| A0386 (298kg) | 13/150/15 | 30cm 3-line | 200m | High | 4 |
| 10360 (134kg) | 15/150/15 | | 100m | High | 9 |
| A0376 (162kg) | 15/150/15 | 30cm 3-line | 100m | High | 9 |
| A0361 (270kg) | 15/150/15 | | 200m | High | 9 |
| A0377 (324kg) | 15/150/15 | 30cm 3-line | 200m | High | 9 |
| A0363 (343kg) | 16/160/15 | 30cm 3-line | 200m | High | 9 |
| A0365 (168kg) | 19/180/15 | | 100m | High | 9 |
| | | | | | |







STIFF STAY PREFABRICATED FARM FENCING





| Heavily Galv. Code (Weight) STIFF STAY [®] HORSE F | Product ENCING | Roll Length | Tensile Strength | Pallet Qty |
|---|-------------------|----------------|---------------------|---------------|
| 10264 (68kg) | 10/90/5 | 50m | High | 9 |
| 10256 (93kg) | 13/122/5 | 50m | High | 9 |

FENCING STIFF STAY Prefabricated Fencing

STIFF STAY®

Stiff Stay prefabricated fencing features a tight cross-over knot manufactured on the Stiff Stay machine. The name Stiff Stay is trademarked to Whites and is made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

The Stiff Stay knot locks the wires in place to resist buckling and sagging. The shape of the knot provides a smooth surface so it is safe and easy to use.

- ✓ Heavily galvanised for longer life
- ✓ Tight cross-over knot
- Resists buckling and sagging
- ✓ Smooth, safe and easy to use
- ✓ High tensile line wires
- ✓ 2.80mm top & bottom wires
- ✓ Available in rolls up to 500m

HORSE FENCE

Whites Rural Stiff Stay Fabricated Horse Fence is specifically designed to be safer for horses. Made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

The tight 5cm picket spacings provide safety from hoof and leg tangling, minimising injuries to horses.

- Smooth clean knot prevents injury to horses
- Smaller aperture mesh
- Resists buckling and sagging

Made to the highest standards using premium grade wire.

Heavily Galvanised features high tensile 2.8mm line wires at top and bottom; 2.5mm high tensile line wires

- & 2.5mm vertical stay wires.
- 10 10 10 10 10 10 10 10 10 10 10 10 Г 10 10 Γ 10 10 10 10/90/5 13/122/5

10

10

10

10

10







FARM FENCING

Manufactured to Australian Standards AS 2423-2002 and zinc coated to AS/NZS 4534-2006. Made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Heavily Galvanised Stiff Stay features high tensile 2.8mm line wires at top and bottom; 2.5mm high tensile line wires with graduated spacings; 2.5mm vertical stay wires.

Also available in Standard Galvanised with 2.5mm top and bottom line wires.







| Heavily Code (| y Galv. Weight) | Standa Code (V | | Product | Roll Length | Tensile Strength | Pallet Qty |
|-------------------|---------------------------|-------------------|---------|----------|----------------|---------------------|---------------|
| STIFF | STAY [®] FABR | ICATED | FARM FE | | | | |
| 10231 | (72kg) | A0201 | (68kg) | 6/70/30 | 200m | High | 9 |
| A0261 | (180kg) | A0221 | (170kg) | 6/70/30 | 500m | High | 4 |
| A0280 | (65kg) | | | 6/70/45 | 200m | High | 9 |
| A0281 | (161kg) | A0224 | (150kg) | 6/70/45 | 500m | High | 4 |
| 10232 | (78kg) | | | 6/90/30 | 200m | High | 9 |
| A0262 | (195kg) | | | 6/90/30 | 500m | High | 4 |
| A0282 | (68kg) | | | 6/90/45 | 200m | High | 9 |
| A0283 | (63kg) | | | 6/90/60 | 200m | High | 9 |
| 10233 | (86kg) | 10203 | (81kg) | 7/90/30 | 200m | High | 9 |
| 10263 | (215kg) | 10223 | (202kg) | 7/90/30 | 500m | High | 4 |
| A0284 | (76kg) | | | 7/90/45 | 200m | High | 9 |
| A0285 | (190kg) | A0225 | (178kg) | 7/90/45 | 500m | High | 4 |
| A0286 | (71kg) | | | 7/90/60 | 200m | High | 9 |
| A0287 | (91kg) | | | 8/80/30 | 200m | High | 9 |
| 10238 | (63kg) | | | 8/90/15 | 100m | High | 9 |
| 10338 | (74kg) | | | 8/90/15 | 100m | High | 9 |
| A0341 | (144kg) | | | 8/90/15 | 200m | High | 4 |
| A0266 | (156kg) | | | 8/90/15 | 250m | High | 4 |
| 10234 | (94kg) | A0204 | (89kg) | 8/90/30 | 200m | High | 9 |
| A0265 | (235kg) | A0264 | (224kg) | 8/90/30 | 500m | High | 4 |
| 10239 | (69kg) | | | 8/115/15 | 100m | High | 9 |
| 10339 | (80kg) | | | 8/115/15 | 100m | High | 9 |
| A0340 | (161kg) | | | 8/115/15 | 200m | High | 4 |
| A0269 | (172kg) | | | 8/115/15 | 250m | High | 4 |
| 10261 | (101kg) | | | 8/115/30 | 200m | High | 9 |







Available with a 30cm hinged apron, for an effective barrier at ground level



| Heavily Galv. Code (Weight) | Product | Hinged Apron | Roll Length | Tensile Strength | Pallet Qty |
|--------------------------------|-------------|-----------------|-------------|---------------------|---------------|
| STIFF STAY® EXCL | USION FENCI | NG | | | |
| 10235 (62kg) | 8/80/15 | | 100m | High | 9 |
| 10238 (63kg) | 8/90/15 | | 100m | High | 9 |
| A0267 (84kg) | 8/90/15 | 30cm 3-line | 100m | High | 9 |
| A0266 (156kg) | 8/90/15 | | 250m | High | 4 |
| A0268 (209kg) | 8/90/15 | 30cm 3-line | 250m | High | 4 |
| 10289 (76kg) | 11/90/15 | | 100m | High | 9 |
| 10285 (97kg) | 11/90/15 | 30cm 4-line | 100m | High | 9 |
| 10251 (86kg) | 13/90/15 | | 100m | High | 9 |
| 10255 (106kg) | 13/90/15 | 30cm 3-line | 100m | High | 9 |
| 10239 (69kg) | 8/115/15 | | 100m | High | 9 |
| A0270 (90kg) | 8/115/15 | 30cm 3-line | 100m | High | 9 |
| A0269 (172kg) | 8/115/15 | | 250m | High | 4 |
| A0271 (225kg) | 8/115/15 | 30cm 3-line | 250m | High | 4 |
| A0390 (258kg) | 11/115/15 | 30cm 3-line | 250m | High | 4 |
| 10259 (92kg) | 13/115/15 | | 100m | High | 9 |
| A0273 (140kg) | 13/115/15 | 30cm 3-line | 100m | High | 9 |
| A0272 (228kg) | 13/115/15 | | 250m | High | 4 |
| A0274 (281kg) | 13/115/15 | 30cm 3-line | 250m | High | 4 |
| A0393 (97kg) | 13/137/15 | | 100m | High | 9 |
| A0391 (118kg) | 13/137/15 | 30cm 3-line | 100m | High | 9 |
| A0394 (241kg) | 13/137/15 | | 250m | High | 4 |
| A0392 (294kg) | 13/137/15 | 30cm 3-line | 250m | High | 4 |
| 10260 (118kg) | 15/150/15 | | 100m | High | 9 |
| A0276 (130kg) | 15/150/15 | 30cm 3-line | 100m | High | 9 |
| A0275 (273kg) | 15/150/15 | | 250m | High | 4 |
| A0277 (325kg) | 15/150/15 | 30cm 3-line | 250m | High | 4 |
| A0278 (651kg) | 15/150/15 | 30cm 3-line | 500m | High | 1 |
| A0395 (343kg) | 16/160/15 | 30cm 3-line | 250m | High | 4 |
| A0279 (134kg) | 19/180/15 | | 100m | High | 9 |
| | | | | | |

| Heavily Galv. Code (Weight) | Product | Roll Length | Tensile Strength | Pallet Qty |
|--------------------------------|-------------|-------------|---------------------|---------------|
| STIFF STAY® EXCLUSION | I FENCE APP | RON ONLY | | |
| A0247 (29kg) | 4/30/15 | 100m | High | 18 |
| HINGED JOINT EXCLUSI | ON FENCE A | PRON ONLY | | |
| A0310 (39kg) | 6/51/15 | 100m | High | 9 |



EXCLUSION FENCING

Narrow 15cm picket spacings for smaller animals and made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Stiff Stay exclusion fencing features:

Premium Coating & Wire Grade

- Heavily Galvanised
- 2.8mm high tensile top and bottom line wires
- 2.5mm high tensile line wires and 2.5mm vertical stay wires

Continuous Vertical Pickets

- Stiff Stay features continuous vertical pickets which are locked into place to resist sagging & buckling
- Compared to hinged joint fencing, they also provide a better fence over undulating land following the contour of the ground

Optional Pre-attached Hinged Apron

- Pre-attached to the bottom line wire with a hinged joint, the apron is a 300mm section of fence laid on the ground, restricting penetration or digging under the fence
- Exclusion fencing without hinged aprons require the fencing to be forced onto the ground, placing unnecessary stress on your fence posts
- The hinged version is both faster to install and easier on the fence, giving it a longer service life
- Also referred to as a hinged footer

Pre-Stripped Roll

- Stiff Stay has the first two pickets and the last two pickets removed from every roll
- A convenient aid for faster installation around end assemblies no need to strip picket wires

Tension Crimps

- Stiff Stay line wires include tension crimps that provide a quick visual when judging the correct tension
- When the crimp is half flattened, the tension is generally sufficient; when no crimp can be seen, then the tension in the wire is too high and needs to be reduced







HINGED JOINT

FENCING

Whites Rural Hinged Joint Prefabricated Farm Fencing is made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

- Ideal for stock, boundary and internal fencing .
- . Flexible knot absorbs stock impact
- 2.50mm high tensile line wires

The strength of the tightly wrapped knot resists livestock pressure while remaining flexible enough to retain its structure. The hinged joint "knot" allows the fence to flex under stock pressure, absorbing the impact of livestock so the fence regains its shape.

Also available in Heavily Galvanised with 2.8mm top and bottom line wires.



Spacing Chart



WILD DOG HINGED JOINT

Tight picket spacings protect against feral animals. High tensile 2.0mm line wires and 2.0mm picket wires, 2.5mm top and bottom wires, heavily galvanised to AS4534.

FARMLITE[™] HINGED JOINT

Farmlite Hinged Joint is a cost-effective solution for hobby farms and smaller rural properties. Made from 2.00mm standard galvanised wires.



| Code | Product | Tensile Strength | Roll Length | Roll Weight | Pallet Qty | Galv. Coating | Line Wire |
|---------|-----------|---------------------|----------------|----------------|---------------|------------------|--------------|
| STANDA | RD GALVAN | ISED HING | ED JOIN | | | | |
| 10291 | 6/70/30 | High | 200m | 70kg | 9 | Standard | 2.5mm |
| 10292 | 6/90/30 | High | 200m | 74kg | 9 | Standard | 2.5mm |
| 10293 | 7/90/30 | High | 200m | 83kg | 9 | Standard | 2.5mm |
| 10294 | 8/90/30 | High | 200m | 92kg | 9 | Standard | 2.5mm |
| 10295 | 8/80/15 | High | 100m | 60kg | 9 | Standard | 2.5mm |
| 10298 | 8/90/15 | High | 100m | 61kg | 9 | Standard | 2.5mm |
| 10299 | 8/115/15 | High | 100m | 69kg | 9 | Standard | 2.5mm |
| HEAVY (| GALVANISE | D HINGED J | IOINT | | | | |
| A0311 | 6/70/30 | High | 200m | 76kg | 9 | Heavy | 2.5mm |
| A0312 | 6/90/30 | High | 200m | 81kg | 9 | Heavy | 2.5mm |
| A0313 | 7/90/30 | High | 200m | 90kg | 9 | Heavy | 2.5mm |
| A0314 | 8/90/30 | High | 200m | 99kg | 9 | Heavy | 2.5mm |
| A0315 | 8/80/15 | High | 100m | 63kg | 9 | Heavy | 2.5mm |
| A0318 | 8/90/15 | High | 100m | 67kg | 9 | Heavy | 2.5mm |
| A0319 | 8/115/15 | High | 100m | 74kg | 9 | Heavy | 2.5mm |

| | Product | | | | | | Top/Base Wire |
|-------|-----------|------|------|------|---|-------|------------------|
| 10287 | 13/115/15 | High | 100m | 56kg | 9 | Heavy | 2.5mm |

| Code FARMLIT | Product E [™] HINGEI | Tensile Strength JOINT | Roll Length | Roll Weight | Pallet Qty | Galv. Coating | Line Wire |
|-----------------|----------------------------------|------------------------------|----------------|----------------|---------------|------------------|--------------|
| 10281 | 8/90/15 | Medium | 100m | 42kg | 9 | Standard | 2.0mm |
| 10282 | 8/115/15 | Medium | 100m | 46kg | 9 | Standard | 2.0mm |
| 10272 | 8/115/15 | Medium | 50m | 24kg | 16 | Standard | 2.0mm |







| Code | Height | Aperture nom. | Wire Dia. nom. | Roll Length | Roll Weight | Pallet Qty | Galv. Coating |
|--------------|---------|---------------|-------------------|----------------|----------------|---------------|------------------|
| HEAVY | IETTING | | | | | | |
| 10451 | 30cm | 4cm | 1.4mm | 50m | 13kg | 48 | Heavy |
| 10452 | 60cm | 4cm | 1.4mm | 50m | 26kg | 18 | Heavy |
| 10454 | 90cm | 4cm | 1.4mm | 50m | 36kg | 9 | Heavy |
| 10474 | 90cm | 4cm | 1.4mm | 100m | 75kg | 9 | Heavy |
| 10455 | 105cm | 4cm | 1.4mm | 50m | 42kg | 9 | Heavy |
| 10475 | 105cm | 4cm | 1.4mm | 100m | 86kg | 9 | Heavy |
| 10456 | 120cm | 4cm | 1.4mm | 50m | 48kg | 9 | Heavy |
| 10458 | 180cm | 4cm | 1.4mm | 50m | 74kg | 9 | Heavy |



| Code HEAVY N | Height ETTING - I | Aperture nom. BOUNDARY | Wire Dia. nom. | Roll Length | Roll Weight | Pallet Qty | Galv. Coating |
|-----------------|----------------------|------------------------------|-------------------|----------------|----------------|---------------|------------------|
| 10653 | 90cm | 5cm | 1.6mm | 50m | 37kg | 9 | Heavy |
| 10655 | 120cm | 5cm | 1.6mm | 50m | 48kg | 9 | Heavy |
| 10657 | 180cm | 5cm | 1.6mm | 50m | 71kg | 9 | Heavy |



RURAL NETTING

Whites Rural Heavy Netting is a versatile heavily galvanised netting for rural and heavy duty applications.

- Reverse twist construction
- Double selvedge wires for added strength
- Heavily galvanised

Netting with a 4cm aperture, 1.4mm wire diameter (often referred to as rabbit netting) & is available in varying heights. Suggested uses are:

- 30cm reconditioning of existing fences, garden edging
 60cm reconditioning of existing fences, poultry
 90cm rabbit proofing, boundary fencing & tree guards
- **105cm** rabbit proofing, boundary fencing & tree guards **120cm** - boundary and feral fencing, poultry
- 180cm feral fencing, poultry and animal enclosures



BOUNDARY NETTING

Whites Rural Heavy Duty Boundary Netting has a 5cm aperture, 1.6mm wire diameter & is available in varying heights. Suggested uses are:

90cm - farm fencing, dogs & tree guards
120cm - feral fencing, animal enclosures & tree guards
180cm - feral fencing, animal enclosures & tennis courts







FARM MESH HEAVY DUTY

Whites Rural Farm Mesh Heavy Duty is a 2.5mm general purpose welded mesh for heavy duty applications.

- Heavy welded construction
- Flush cut edges
- 2.5mm galvanised wire

Whites Rural Farm Mesh can be used for a variety of applications, including:

- Cages and animal enclosures Drainage grids
- Fencing and tree guards Trailer enclosures

FARM MESH HEAVY DUTY HEAVILY GALVANISED

A heavily galvanised version of the Whites Rural Farm Mesh Heavy Duty.

- Heavily galvanised to AS4534
- 75mm x 50mm aperture
- 2.5mm for heavy duty applications
- Heavy welded construction
- Flush cut edges



DOG MESH HEAVY DUTY

Whites Rural Dog Mesh Heavy Duty is an ideal fencing mesh to keep larger dogs and similar sized animals within a boundary, or out of garden beds and yards.

- Graduated mesh
- Heavy welded construction
- Flush cut edges
- 2.5mm galvanised wire

Line and picket wires have been strengthened for added rigidity. The graduated mesh is available in 120cm & 180cm heights, with smaller apertures at the base to fence puppies and smaller animals.











| Code | Height (cm) | Aperture (mm) | Wire Diameter | Roll Length | Roll Weight | Pallet Qty | Galv. Coating |
|-------|-----------------|------------------|------------------|----------------|----------------|---------------|------------------|
| HEAVY | DUTY FAI | RM MESH | | | | | |
| 21982 | 90 | 75 x 50 | 2.5mm | 30m | 34kg | 9 | Standard |
| 21983 | 120 | 75 x 50 | 2.5mm | 30m | 46kg | 9 | Standard |
| 21988 | 180 | 75 x 50 | 2.5mm | 30m | 69kg | 9 | Standard |
| 21980 | 90 | 100 x 100 | 2.5mm | 30m | 22kg | 16 | Standard |
| 21981 | 120 | 100 x 100 | 2.5mm | 30m | 29kg | 16 | Standard |
| 21989 | 180 | 100 x 100 | 2.5mm | 30m | 43kg | 9 | Standard |
| HEAVY | DUTY FAR | RM MESH - H | EAVILY GAI | VANISED | | | |
| 22683 | 90 | 75 x 50 | 2.5mm | 30m | 34kg | 9 | Heavy |
| 22684 | 120 | 75 x 50 | 2.5mm | 30m | 46kg | 9 | Heavy |
| HEAVY | DUTY DO | G MESH | | | | | |
| 22004 | 120 | Graduated | 2.5mm | 30m | 23kg | 16 | Standard |
| 22008 | 180 | Graduated | 2.5mm | 30m | 32kg | 16 | Standard |







6m Length

| Code | Aperture (mm) | Width (mm) | Length (m) | Weight | Wire Dia. (mm) | Туре |
|---------|------------------|---------------|---------------|--------|-------------------|---------|
| SHEEP Y | ARD MESH | | | | | |
| ASYM1 | 100 x 250 | 900 | 6 | 12.7kg | 5 | Medium |
| ASYM2 | 100 x 250 | 1100 | 6 | 15.3kg | 5 | Medium |
| ASYM3 | 100 x 200 | 900 | 6 | 13.5kg | 5 | Heavy |
| ASYM4 | 100 x 200 | 1100 | 6 | 16.3kg | 5 | Heavy |
| ASYM5 | 100 x 150 | 900 | 6 | 14.9kg | 5 | X Heavy |
| ASYM6 | 100 x 150 | 1100 | 6 | 18kg | 5 | X Heavy |
| ASYM7 | 100 x 250 | 900 | 6 | 15.8kg | 5.6 | Medium |
| ASYM8 | 100 x 250 | 1100 | 6 | 19.1kg | 5.6 | Medium |
| ASYM9 | 150/100 x 250 | 900 | 6 | 10.6kg | 4/5 | Light |



| Code | Aperture (mm) | Width (mm) | Length (mm) | Weight | Nom. Wire Dia. |
|---------|------------------|---------------|----------------|--------|-------------------|
| GENERAL | PURPOSE MESH | PANELS | | | |
| 21898 | 25 x 25 | 1200 | 2400 | 7.3kg | 2.25mm |
| 21888 | 25 x 25 | 1200 | 2400 | 7.9kg | 2.5mm |
| 21880 | 50 x 50 | 1200 | 2400 | 5.7kg | 3.15mm |
| 21897 | 75 x 50 | 1200 | 2400 | 7.8kg | 3.5mm |
| 21887 | 75 x 50 | 1200 | 2400 | 9.2kg | 4mm |
| 21896 | 100 x 100 | 1200 | 2400 | 6.1kg | 4mm |
| 21886 | 100 x 100 | 1200 | 2400 | 9kg | 5mm |



FENCING WELDED MESH Sheep Yard, General & Tree Guards

SHEEP YARD MESH

Whites Rural Sheep Yard Mesh products are manufactured flush with the outside edge of the perimeter wires. Made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Light: 900mm high - the top two vertical apertures are set at 150mm and the lower six at 100mm. Horizontal 250mm apertures. 5mm line wires, 4mm cross wires.

Medium: 5mm wire with vertical apertures at 100mm and horizontal apertures set at 250mm. Also produced in a 5.6mm wire for special orders.

Heavy: 5mm wire with vertical apertures at 100mm and horizontal apertures set at 200mm.

Extra Heavy: 5mm wire with vertical apertures at 100mm and horizontal apertures set at 150mm.



GENERAL PURPOSE

Whites Rural General Purpose Welded Mesh panels are manufactured in a range of sizes from wire and are produced to Australian Standards. The mesh is finished flush all around for safety and to make joining easy.

Ideal for Animal Enclosures, Cages, Trailer Enclosures, Fencing, Tree Guards, Window Guards, Safety Screens, Drainage Grids, Shelves, Racks & Partitions.

- Flush cut edges on all sides
- Medium tensile galvanised wire

TREE GUARD

Whites Rural Tree Guard is a heavy duty enclosure to protect young trees. Tree Guard is rolled before delivery and arrive ready for installation.

Made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.



SPECIALIST RANGE

HORTICULTURE Agri-Wire Trellis & Accessories



AGRI-WIRE[®] TRELLIS WIRE

Whites Rural Heavily Galvanised Agri-Wire High Tensile Trellis Wire is made in Australia to the highest standards, exclusively from Whites Albury manufacturing plant in regional Australia, using premium grade wire.

- Heavily galvanised to last up to 4 times longer
- Produced to the highest tolerance
- Smooth tangle free delivery



Coil

2000m

1000m

1000m

1000m

Coil

44kg

44kg

50kg

61kg

Sling

Qt

10

10

10

10

Hvy Gal

Hvy Gal

Hvy Gal

Hvy Gal

Rec. Tension

cina St

1.0kn, 2.7kn

2.0kn, 6.0kn

2.2kn, 8.3kn

3.1kn, 9.4kn

Carton Qty

40

Tensile

Hiah

High

High

High



AGRI-WIRE® STRAINER

Whites Rural Agri-Wire Strainer is a specialised strainer for trellis wire in vineyards. Featuring a traditional cam-lock mechanism, the Agri-Wire Strainer's design makes it an easy and effective device for straining wire at the end of trellis.

Suitable for all high tensile wires up to 3.15mm and ideal for use with Whites Rural Agri-Wire Trellis Wire.



Product

Agri-Wire Strainer

12104

Wire

2.00mm

2.65mm

2.85mm

3.15mm

10022

10023

10024

10026



AGRI-CLIP[™]

Whites Rural Agri-Clips are specially design to fit most steel fence post. Installed in seconds, proven a fast and easy way to hold and support permanent and semi-permanent trellis wires. Made from tough, durable nylon material.

Suitable for all high tensile wires up to 3.15mm and suits Stockpost and Stockpost XL.



| Qty |
|-----|
| |
| 20 |
| 20 |
| |







| Code | mm (ft) | (mm) | Туре | Weight | (Nom. mm) |
|---------|----------------------------|------|------|--------|-----------|
| TOP NOT | CH [™] FARM GATES | S | | | |
| 13122 | 875 (2'8") | 825 | - | 8kg | 200x100x5 |
| 13123 | 1075 (3'3") | 1025 | - | 9kg | 200x100x5 |
| 13124 | 1220 (4'0") | 1170 | - | 10kg | 200x100x5 |
| 13105 | 1525 (5'0") | 1475 | - | 13kg | 200x100x5 |
| 13106 | 1830 (6'0") | 1780 | - | 14kg | 200x100x5 |
| 13108 | 2440 (8'0") | 2390 | "[" | 20kg | 200x100x5 |
| 13110 | 3050 (10'0") | 3000 | "[" | 22kg | 200x100x5 |
| 13112 | 3660 (12'0") | 3610 | "[" | 26kg | 200x100x5 |
| 13132 | 3660 (12'0") | 3610 | "]]" | 29kg | 200x100x5 |
| 13114 | 4270 (14'0") | 4220 | "[]" | 31kg | 200x100x5 |
| 13116 | 4880 (16'0") | 4830 | "[]" | 36kg | 200x100x5 |

Nominal Size is the recommended gate opening

| Code | Nominal mm (ft) | Actual (mm) | Stay Type | Weight | Pipe Mesh (Nom. mm) |
|----------|--------------------|----------------|--------------|--------|------------------------|
| 5 BAR FA | ARM GATES | | | | |
| 13204 | 1220 (4'0") | 1170 | - | 13kg | 25NB |
| 13205 | 1525 (5'0") | 1475 | - | 16kg | 25NB |
| 13206 | 1830 (6'0") | 1780 | - | 18kg | 25NB |
| 13208 | 2440 (8'0") | 2390 | " " | 25kg | 25NB |
| 13210 | 3050 (10'0") | 3000 | " " | 29kg | 25NB |
| 13212 | 3660 (12'0") | 3610 | " " | 34kg | 25NB |
| 13214 | 4270 (14'0") | 4220 | " " | 41kg | 25NB |
| 13216 | 4880 (16'0") | 4830 | " " | 46kg | 25NB |



TOP NOTCH[™] "I" STAY GATES

Whites Rural Top Notch Gates are manufactured with embedded mesh that sits inside of the gate. Along with end welds that are smooth and flush with the pipe, it makes for a stronger, safer and faster hanging gate.

Inbuilt Strength

Embedded wire mesh increases strength, improves durability.

Edge Protect

Safer for hands and livestock. No sharp edges!

Fast Fit

No need to cut wire mesh. Hinges fit fast!







- All pipe is a uniform 25NB
- 1145mm high, 2400-4800mm wide
- 5mm galvanised wire
- 200mm horizontal x 100mm vertical aperture
- Zinc-based coating completely covers pipe & welds
- Supplied with our "Shut the gate mate!" sign

Whites Rural Farm Gates are made to exacting standards from some of the best materials available, quality tested to ensure trouble-free fencing that is designed to last.

5 BAR FARM GATES

Whites Rural 5 Bar Farm Gates are made stronger for cattle and high pressure livestock situations, featuring horizontal hot-dipped galvanised pipe welded to the outer frame.

- All pipe is a uniform 25NB
- 1145mm high, 1000-4800mm wide
- Zinc-based coating completely covers pipe & welds







"N" STAY FARM GATES

Whites Rural "N" Stay Farm Gates feature 200mm x 75mm mesh size for increased strength and protection. With a diagonal brace running from bottom to top corner, the range is available in left and right hand options (pack of 5 - 3L/2R).

- All pipe is a uniform 25NB
- 1145mm high, 3000-4800mm wide
- 5mm galvanised wire
- 200mm horizontal x 75mm vertical aperture
- Zinc-based coating completely covers pipe & welds
- Supplied with our "Shut the gate mate!" sign

Consistently high quality gates manufactured from high quality galvanised pipe. The pipe is galvanised on the inside as well as the outside to provide maximum protection and a long working life.



COLLARED FARM GATES

Whites Rural Collared Farm Gates recognise the specific needs of the WA rural market. A range of regular, "I" stay & "V" stay gates has been developed with a pre-fitted collar as distinctly used in Western Australia farming communities.

- All pipe is a uniform 25NB
- 1145mm high, 2400-4800mm wide
- 5mm galvanised wire
- 200mm horizontal x 100mm vertical aperture
- Zinc-based coating completely covers pipe & welds
- Supplied with our "Shut the gate mate!" sign



Nominal Size is the recommended gate opening

200mm x 75mm

| Code "N" STAY | Nominal mm (ft) / FARM GATES | Actual (mm) | Stay Type | Weight | Weld Mesh (Nom. mm) |
|------------------|------------------------------------|----------------|--------------|--------|------------------------|
| 13510 | 3050 (10'0") | 3000 | "N" | 27kg | 200x75x5 |
| 13512 | 3660 (12'0") | 3610 | "N" | 30kg | 200x75x5 |
| 13514 | 4270 (14'0") | 4220 | "N" | 34kg | 200x75x5 |
| 13516 | 4880 (16'0") | 4830 | "N" | 38kg | 200x75x5 |



| Code | Nominal mm (ft) | Actual (mm) | Stay Type | Weight | Weld Mesh (Nom. mm) |
|--------|--------------------|----------------|--------------|--------|------------------------|
| COLLAR | ED "I" STAY FARM | GATES (WA | ONLY) | | |
| 13403 | 1075 (3'3") | 1025 | - | 9kg | 200x100x5 |
| 13404 | 1220 (4'0") | 1170 | - | 10kg | 200x100x5 |
| 13405 | 1525 (5'0") | 1475 | - | 13kg | 200x100x5 |
| 13406 | 1830 (6'0") | 1780 | - | 14kg | 200x100x5 |
| 13408 | 2440 (8'0") | 2390 | " " | 20kg | 200x100x5 |
| 13410 | 3050 (10'0") | 3000 | " " | 22kg | 200x100x5 |
| 13412 | 3660 (12'0") | 3610 | " " | 26kg | 200x100x5 |
| 13414 | 4270 (14'0") | 4220 | " " | 31kg | 200x100x5 |
| 13416 | 4880 (16'0") | 4830 | " " | 36kg | 200x100x5 |
| COLLAR | ED "V" STAY FARM | I GATES (WA | ONLY) | | |
| 13710 | 3050 (10'0") | 3000 | "V" | 22kg | 200x100x5 |
| 13712 | 3660 (12'0") | 3610 | "V" | 26kg | 200x100x5 |
| 13714 | 4270 (14'0") | 4220 | "V" | 31kg | 200x100x5 |
| 13716 | 4880 (16'0") | 4830 | "V" | 36kg | 200x100x5 |









BLUE LABEL FARM GATES

Whites Rural Blue Label Farm Gates have been manufactured by Whites' Albury Manufacturing in regional Australia. Years of experience and commitment to the gate industry re-assures farmers and contractors that Whites' Albury Manufacturing gates are the right choice for a high quality gate.

All Blue Label Farm Gates feature:

- 5mm pre-galvanised wire mesh
- 150mm horizontal x 100mm vertical aperture
- 350 grade high tensile 25NB pipe
- Fully welded joints to resists joint cracking
- 1170mm high

Pipe is hot-dipped galvanised to Australian Standards. Available in "I", "II", "III" and "IIII" stays, as well as in "V", "N" and "M" stays, depending on gate length.



Nominal Size is the recommended gate opening

| Upright Code | Stay Type | Weight (kg) | N Stay Code | Stay Type | Weight (kg) | Nominal mm (ft) | Actual (mm) | Mesh (mm) |
|-----------------|--------------|----------------|----------------|--------------|----------------|--------------------|----------------|--------------|
| BLUE L | ABEL | FARM GA | TES | | | | | |
| AMS03 | - | 9 | - | - | - | 915 (3'0") | 865 | 150x100x5 |
| AMS04 | - | 11 | - | - | - | 1220 (4'0") | 1170 | 150x100x5 |
| AMS05 | "[" | 14 | - | - | - | 1525 (5'0") | 1475 | 150x100x5 |
| AMS06 | "[" | 16 | - | - | - | 1830 (6'0") | 1780 | 150x100x5 |
| AMS07 | "[" | 18 | - | - | - | 2135 (7'0") | 2085 | 150x100x5 |
| AMS08 | "[" | 19 | AVG08 | "V" | 22 | 2440 (8'0") | 2390 | 150x100x5 |
| AMS09 | "[" | 21 | AVG09 | "V" | 24 | 2745 (9'0") | 2695 | 150x100x5 |
| AMS10 | "[" | 23 | ANS10 | "N" | 27 | 3050 (10'0") | 3000 | 150x100x5 |
| AMS11 | "I" | 25 | ANS11 | "N" | 29 | 3350 (11'0") | 3300 | 150x100x5 |
| AMS12 | "[" | 27 | ANS12 | "N" | 31 | 3660 (12'0") | 3610 | 150x100x5 |
| AMSD2 | "II" | 29 | - | - | - | 3660 (12'0") | 3610 | 150x100x5 |
| AMS13 | "II" | 31 | ANS13 | "N" | 33 | 3960 (13'0") | 3910 | 150x100x5 |
| AMS14 | "11" | 32 | ANS14 | "N" | 36 | 4270 (14'0") | 4220 | 150x100x5 |
| AMS15 | "111" | 36 | ANS15 | "N" | 38 | 4570 (15'0") | 4520 | 150x100x5 |
| AMS16 | "111" | 38 | ANS16 | "N" | 40 | 4880 (16'0") | 4830 | 150x100x5 |
| AMS18 | "111" | 42 | ANS18 | "N" | 44 | 5485 (18'0") | 5435 | 150x100x5 |
| AMS20 | "1111" | 48 | ANS20 | "M" | 52 | 6095 (20'0'') | 6045 | 150x100x5 |
| | | | | | | , , | | |





XHD FARM GATES

Whites Rural Orange Label XHD Farm Gates feature outer frames made with 32NB x 2.6mm high tensile pipe for an extra heavy duty gate. Made in Whites' Albury Manufacturing plant in regional Australia.



STOCKYARD FARM GATES

Whites Rural Green Label Stock Yard Farm Gates are the premium gate for cattle and high pressure livestock farming. Made in Whites' Albury Manufacturing plant in regional Australia.

Green Label Stock Yard Farm Gates feature:

- 32NB x 2.6mm high tensile pipe frame
- 7 bar gate: 5 x 25NB internal rails
- 20mm through-frame sliding bolt
- 1370mm high



| WHITES |
|--------|
| RURAL |
| |

| - | | | | | | | _ | | | | _ | | | | _ |
|---|---|-----|---|---|---|-------|---|-----|---|---|-------|-------|---|-------|---|
| _ | | | | | - | | | | | 1 | | | | | _ |
| | | | | | | | | | | - | | | _ | - | - |
| + | | | - | | - | - | - | | - | - | _ | - | | | - |
| | - | - | - | - | - | | - | | - | - | | | | - | |
| + | | - | | - | - | | | | - | - | - | - | | | |
| | | + + | | - | - | | | - H | - | - | | | | | - |

Upright gates available with a crossbar for extra strength Nominal Size is the recommended gate opening

| Code | Nominal mm (ft) | Actual (mm) | Weight | Stay Type | Frame Pipe | Stay Type | Mesh (mm) |
|----------------|--------------------|----------------|--------|--------------|---------------|--------------|--------------|
| | TAY FARM GAT | | | | | | |
| AXV08 | 2440 (8'0") | 2390 | 23kg | "V" | 32NB | 25NB | 150x100x5 |
| AXN10 | 3050 (10'0") | 3000 | 33kg | "N" | 32NB | 25NB | 150x100x5 |
| AXN12 | 3660 (12'0") | 3610 | 40kg | "N" | 32NB | 25NB | 150x100x5 |
| AXN14 | 4270 (14'0") | 4220 | 47kg | "N" | 32NB | 25NB | 150x100x5 |
| AXN16 | 4880 (16'0") | 4830 | 53kg | "N" | 32NB | 25NB | 150x100x5 |
| XHD UPF | RIGHT FARM G | ATES | | | | | |
| AXM08 | 2440 (8'0") | 2390 | 26kg | "[" | 32NB | 32NB | 150x100x5 |
| AXM10 | 3050 (10'0") | 3000 | 31kg | "[" | 32NB | 32NB | 150x100x5 |
| AXM12 | 3660 (12'0") | 3610 | 35kg | "[" | 32NB | 32NB | 150x100x5 |
| AXMD2 | 3660 (12'0") | 3610 | 39kg | "II" | 32NB | 32NB | 150x100x5 |
| AXM14 | 4270 (14'0") | 4220 | 41kg | "11" | 32NB | 32NB | 150x100x5 |
| AXM16 | 4880 (16'0") | 4830 | 48kg | "111" | 32NB | 32NB | 150x100x5 |
| XHD UPF | RIGHT FARM G | ATES - C | ROSSBA | R | | | |
| AXB08 | 2440 (8'0") | 2390 | 30kg | "[" | 32NB | 32NB | 150x100x5 |
| AXB10 | 3050 (10'0") | 3000 | 36kg | "[" | 32NB | 32NB | 150x100x5 |
| AXB12 | 3660 (12'0") | 3610 | 42kg | "[" | 32NB | 32NB | 150x100x5 |
| AXB14 | 4270 (14'0") | 4220 | 50kg | "II" | 32NB | 32NB | 150x100x5 |
| AXB16 | 4880 (16'0") | 4830 | 59kg | "111" | 32NB | 32NB | 150x100x5 |

| |
|------|
| |

Supplied with a 20mm through-frame sliding bolt

| Nominal Size is the recommended gate op | pening |
|---|--------|
|---|--------|

| Code | Nominal mm (ft) | Actual (mm) | Weight | Strap 50x5mm | Frame Pipe | Internal Rails |
|--------|--------------------|----------------|--------|-----------------|---------------|-------------------|
| STOCKY | ARD FARM GA | TES | | | | |
| ABY03 | 915 (3'0") | 865 | 16kg | - | 32NB | 25NB |
| ABY04 | 1220 (4'0") | 1170 | 21kg | - | 32NB | 25NB |
| ABY05 | 1525 (5'0") | 1475 | 26kg | - | 32NB | 25NB |
| ABY06 | 1830 (6'0") | 1780 | 34kg | 1 Strap | 32NB | 25NB |
| ABY07 | 2135 (7'0") | 2085 | 36kg | 1 Strap | 32NB | 25NB |
| ABY08 | 2440 (8'0") | 2390 | 39kg | 1 Strap | 32NB | 25NB |
| ABY09 | 2745 (9'0") | 2695 | 42kg | 1 Strap | 32NB | 25NB |
| ABY10 | 3050 (10'0") | 3000 | 45kg | 1 Strap | 32NB | 25NB |
| ABY11 | 3350 (11'0") | 3300 | 50kg | 1 Strap | 32NB | 25NB |
| ABY12 | 3660 (12'0") | 3610 | 55kg | 2 Straps | 32NB | 25NB |
| ABY13 | 3960 (13'0") | 3910 | 59kg | 2 Straps | 32NB | 25NB |
| ABY14 | 4270 (14'0") | 4220 | 63kg | 2 Straps | 32NB | 25NB |
| ABY15 | 4570 (15'0") | 4520 | 69kg | 3 Straps | 32NB | 25NB |
| ABY16 | 4880 (16'0") | 4830 | 74kg | 3 Straps | 32NB | 25NB |





| |
|------|
| |
| |

Nominal Size is the recommended gate opening

| Code | Nominal mm (ft) | Actual (mm) | Weight | Strap 32x5mm | Height (mm) | Frame Pipe | Internal Rails |
|-------|--------------------|----------------|--------|-----------------|----------------|---------------|-------------------|
| SHEEP | YARD FARM G | ATES | | | | | |
| ABS03 | 915 (3'0") | 865 | 7kg | - | 990 | 25NB | 20NB |
| ABS04 | 1220 (4'0") | 1170 | 11kg | - | 990 | 25NB | 20NB |
| ABS06 | 1830 (6'0") | 1780 | 20kg | 1 Strap | 990 | 25NB | 20NB |
| ABS08 | 2440 (8'0") | 2390 | 27kg | 1 Strap | 990 | 25NB | 20NB |
| ABS10 | 3050 (10'0") | 3000 | 34kg | 1 Strap | 990 | 25NB | 20NB |
| ABS12 | 3660 (12'0") | 3610 | 43kg | 2 Straps | 990 | 25NB | 20NB |



Nominal Size is the recommended gate opening

| Code | Nominal mm (ft) | Actual (mm) | Weight | Stay Type | Height (mm) | Mesh (mm) |
|---------|--------------------|----------------|--------|--------------|----------------|--------------|
| HORSE | MESH FARM GAT | | | | | |
| AHI03 | 915 (3'0") | 865 | 5kg | - | 1170 | 100x50x5 |
| AHI04 | 1220 (4'0") | 1170 | 6kg | - | 1170 | 100x50x5 |
| AHI06 | 1830 (6'0") | 1780 | 9kg | "I" | 1170 | 100x50x5 |
| AHI08 | 2440 (8'0") | 2390 | 12kg | "I" | 1170 | 100x50x5 |
| AHI10 | 3050 (10'0") | 3000 | 15kg | "I" | 1170 | 100x50x5 |
| AHI12 | 3660 (12'0") | 3610 | 18kg | "I" | 1170 | 100x50x5 |
| AHI13 | 3660 (12'0") | 3610 | 18kg | "11" | 1170 | 100x50x5 |
| AHI14 | 4270 (14'0") | 4220 | 22kg | "11" | 1170 | 100x50x5 |
| AHI16 | 4880 (16'0") | 4830 | 25kg | "111" | 1170 | 100x50x5 |
| AHI17 | 5182 (17'0") | 5180 | 33kg | "111" | 1170 | 100x50x5 |
| HORSE I | MESH FARM GAT | ES - N STA | Y | | | |
| AHN10 | 3050 (10'0") | 3000 | 15kg | "N" | 1170 | 100x50x5 |
| AHN12 | 3660 (12'0") | 3610 | 18kg | "N" | 1170 | 100x50x5 |
| AHN14 | 4270 (14'0") | 4220 | 22kg | "N" | 1170 | 100x50x5 |
| AHN16 | 4880 (16'0") | 4830 | 24kg | "N" | 1170 | 100x50x5 |
| HORSE I | MESH FARM GAT | ES - V STA | Y | | | |
| AHV08 | 2440 (8'0") | 2390 | 15kg | "V" | 1170 | 100x50x5 |



SHEEP YARD FARM GATES

Whites Rural Purple Label Sheep Yard Farm Gates feature:

- 25NB high tensile pipe frame
- 7 bar gate: 5 x 20NB internal rails
- Fully welded joints
- Hot-dipped galvanised pipe



HORSE MESH FARM GATES

Whites Rural White Label Horse Mesh Farm Gates feature a smaller aperture mesh specifically designed to be safer for horses.

- 25NB high tensile pipe frame and braces
- 50mm horizontal x 100mm vertical aperture
- 5mm pre-galvanised wire welded mesh
- Hot-dipped galvanised pipe, fully welded joints



24





BALLIMORE FARM GATES

Whites Rural Ballimore Farm Gates are significantly stronger 'I' stay gates due to their full-length bar and double 'I' stay top. The robust design is also one of the most visually appealing gates available. Made in Albury, Australia.

Ballimore Farm Gates feature:

- Full-length 25NB top bar, double 'l' stay top
- 25NB high tensile pipe frame and brace
- 150mm horizontal x 100mm vertical aperture
- 5mm pre-galvanised wire mesh
- Hot-dipped galvanised pipe to Australian Standards



FERAL "I" STAY FARM GATES

Whites Rural Feral Farm Gates are designed to keep stock safe and prevent predators boasting an increased overall height of 1660mm and tighter mesh spacings along the base. Made in Albury, Australia.

Feral Farm Gates feature:

- 1660mm overall height
- 50mm horizontal x 100mm vertical aperture along base
- 25NB high tensile pipe frame and brace
- 150mm horizontal x 100mm vertical aperture top
- 5mm pre-galvanised wire mesh
- Hot-dipped galvanised pipe to Australian Standards





CHAIN MESH GATE

Whites Chain Mesh Pedestrian Gate is a popular gate to suit chain wire mesh fences.

| - | | - | <u>n</u> | - | - | - | | and the second second | - | - | - | - |
|---|------|---|----------|---|---|---|---|-----------------------|---|---|---|---|
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | 1 | | | | | | | | | - |
| | | | 1 | | | | - | | | | | - |
| | | _ | - | - | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | 0.1 | | | | |
| | | 1 | 1 | - | | 1 | | | | | | - |
| | | | - | - | | | | | | | | |
| | | | - | - | | - | - | - | | | | |
| | | | | | | | | | | | | |

| Code | Nominal mm (ft) | Actual (mm) | Stay Type | Weight | Height (mm) | Mesh (mm) |
|---------|--------------------|----------------|--------------|--------|----------------|--------------|
| BALLIMC | RE FARM GAT | ES | | | | |
| ABA10 | 3050 (10') | 3000 | "[" | 27kg | 1170 | 150x100x5 |
| ABA12 | 3660 (12') | 3610 | "]]" | 31kg | 1170 | 150x100x5 |
| ABA14 | 4270 (14') | 4220 | "II" | 36kg | 1170 | 150x100x5 |
| ABA16 | 4880 (16') | 4830 | "III" | 40kg | 1170 | 150x100x5 |



| Code | Nominal mm (ft) | Actual (mm) | Stay Type | Weight | Mesh (mm) |
|---------|--------------------|----------------|--------------|--------|--------------|
| FERAL " | I" STAY FARM GA | TES | | | |
| 13012 | 3660 (12') | 3610 | "[" | 52kg | 150x100x5 |
| 13014 | 4270 (14') | 4220 | "[]" | 62kg | 150x100x5 |



| Code | Actual Length x Height (mm) | Weight |
|----------|-----------------------------|--------|
| CHAIN ME | SH GATE | |
| 13100 | 900 x 1800 (3' x 6') | 13.5kg |





Ring Latch



| Ring Latch Code | Drop Latch Code | Product | Pack | Carton Qty | Weight |
|-----------------------|-----------------------|--------------------------|------|---------------|--------|
| GATE FITT | ING SET - | RING LATCH & DROP LATCH | | | |
| 13801 | - | General Purpose Pack | FG1 | 5 | 1.9kg |
| 13802 | 13822 | Economy Pack | FG2 | 10 | 1.6kg |
| 13804 | 13824 | Heavy Duty Long Pack | FG4 | 5 | 2.6kg |
| 13809 | 13829 | Heavy Duty Pack | FG9 | 5 | 2.5kg |
| 13815 | 13825 | Multi-Fit Pack | FG15 | 10 | 1.3kg |
| 13821 | 13820 | Collared Gates (WA only) | FG20 | 5 | 2.6kg |



GATE FITTING SETS

A wide range of galvanised steel gate fitting sets, all the components included. Hang everything from small pedestrian gates to the largest farm gates.

Available in Drop Latch and Ring Latch:

FG1 General Purpose Pack

- Screw-in 12mm latch and catch (ring latch only)
- Top through-post strap 16mm x 300mm thread length including backing plate
- Screw-in bottom gudgeon

FG2 Economy Pack

- Screw-in 12mm latch and catch
- Top strap assembly
- Screw-in 20mm bottom gudgeon

FG4 Heavy Duty Long Pack

- Screw-in 12mm latch and catch
- Top through-post strap 16mm x 400mm thread length including backing plate
- Bottom through-post gudgeon 16mm x 400mm thread length (all nuts and washers included)

FG9 Heavy Duty Pack

- Screw-in 12mm latch and catch
- Top through-post strap 16mm x 300mm thread length including backing plate
- Bottom through-post gudgeon 16mm x 300mm thread length (all nuts and washers included)

FG15 Multi-Fit Pack

- Screw-in 12mm latch and catch
- Top strap assembly
- Screw-in / weld-on bottom gudgeon

FG20 Collared Pack (WA only)

- Screw-in 12mm latch and catch
- Top and bottom through-post hinge assemblies 20mm x 400mm thread length with U-shaped hinge (all nuts and washers included)





INDIVIDUAL FITTINGS

Galvanised steel screw-in and weld-on gate fittings.

Latches

Screw-on available in drop and ring types.

Weld-on drop latch suitable for square or round posts. Can be screw-fixed. Low profile safer for animals.

Strap and Gudgeon

Top strap screw-in type.

WG34 gudgeon weld-on type.

G13 gudgeon features long plate - weld-on or screw-in.

Pins and Sleeves

Featuring pin-lock hole for added peace of mind where needed. Simply weld into place.

Each packs contains 2 pairs (2 x pins and 2 x sleeves)

Double Gate Bow

Self-locating latch for double end gates. Suits 25NB gates.

Cattle Yard Slam Latch

Tough and durable weld-on latch and striker plate for cattle yard fencing. Quick access, locks strong.

SPECIALTY GATE FITTINGS

End Assembly Gate Fittings

Designed for the Stockpost Anchor Post, the fittings attach around the anchor post with no screwing or welding required.

Top strap & gudgeon pack to hinge the gate; drop latch pack to lock the gate.

Bolt-on Double Gate Latch

Robust fitting suitable for securing 25NB double gates. No need for screwing or welding; just position the latch on the gate frame and tighten the bolt to attach.

Pedestrian Gate Pack

Use with pedestrian gates, the pack features an easy access "D" latch and all the components.



| Code | Product | Туре |
|----------|----------------------------|-----------------|
| INDIVIDU | AL FITTINGS | |
| 13830 | Ring Latch & Catch | Screw |
| 13833 | Drop Latch & Eyelet | Screw |
| 13862 | Top Strap 25mm S3 | Screw / Weld-on |
| 13873 | Gudgeon 25mm G13 | Screw / Weld-on |
| 13875 | Gudgeon 25mm WG34 | Weld-on |
| 13895 | Pins & Sleeves 27mm | Weld-on |
| 13896 | Pins & Sleeves 20mm | Weld-on |
| 13897 | Pins & Sleeves 16mm | Weld-on |
| 13898 | Drop Latch | Weld-on |
| DOUBLE | GATE BOW | |
| 13850 | Double Gate Bow | Screw |
| SLAM LA | тсн | |
| 13843 | Slam Latch 20mm | Weld-on |
| 13844 | 6mm Striker Plate 75x100mm | Weld-on |









Carton Code Product Qty Weight 13855 End Assembly Top Strap & Gudgeon 5 1.5kg 13856 5 0.8kg End Assembly Drop Latch & Eyelet Bolt-on Double Gate Latch 13892 20 0.7kg "D" Latch Gate Pack 13790 20 0.7kg









| CONTRACTOR GRADE - LIFTER, DRIVERS & WIRE SPINNER 12207 Contractor Grade 'Grip & Lift' Post Lifter 5.2kg 12203 Contractor Grade Post Driver 9kg 12205 XL Contractor Grade Post Driver 10kg | Code | Product | Weight |
|--|-------|--|--------|
| 12203Contractor Grade Post Driver9kg12205XL Contractor Grade Post Driver10kg | | | weight |
| 12205 XL Contractor Grade Post Driver 10kg | 12207 | Contractor Grade 'Grip & Llft' Post Lifter | 5.2kg |
| 5 | 12203 | Contractor Grade Post Driver | 9kg |
| 12111 Three-Way Wire Spinner 18kg | 12205 | XL Contractor Grade Post Driver | 10kg |
| ······ | 12111 | Three-Way Wire Spinner | 18kg |



| | Product | Weight |
|-------|-------------------------------------|--------|
| STAND | ARD - LIFTER, DRIVER & WIRE SPINNER | |
| 12200 | Post Lifter | 8.3kg |
| 12201 | 800mm Post Driver | 6.8kg |
| 12110 | Wire Spinner | 11.5kg |

TOOLS

DRIVER, LIFTER & SPINNER Contractor & Standard

CONTRACTOR GRADE

Contractor "Grip & Lift" Post Lifter

Robustly designed post lifter featuring parallel gripping surface with hardened steel grips. Heavy duty contractor grade construction.

- Hardened steel grips
- Suits most fence posts including Stockpost XL
- Galvanised steel; high tensile bolts

Contractor Post Drivers

Designed with reinforced handles and unique anti-shake handle to reduce vibrations transferred to the operator. Available in two sizes to suit standard posts and larger intermediate posts. Features include:

- Reinforced fully welded handles
- Balanced handles and head, reduces strain
- Anti-vibration collar

Three-Way Wire Spinner

Heavy Duty Three-Way Wire Spinner for smooth payout of plain & barbed wire. Zinc-plated, heavy duty steel construction. Made tough for Australian conditions.

Three different configurations make for an all-in-one tool to make fencing faster:

- 1. Fence Wire Spinner Large diameter suits all fence wire types
- 2. Barbed Wire Spinner Suitable for all types of barbed wire on reels
- 3. Mobile Hand-Cart Turn unit on side for a mobile barbed wire hand-cart

STANDARD

Whites Rural Standard range of lifter, driver and wire spinner are an economical alternative to the contractor range, available in a durable zinc-plated finish.

Post Lifter

Heavy steel construction. Simply place post in jaw and use the lever action to easily remove steel posts.

Post Driver

Heavy steel construction, weighted balanced head.

Fence Wire Spinner

Central hub is designed for smooth, easy payout, and is adjustable to reduce spin and overrun for faster payout. Includes barbed wire attachment.



STRAINERS Straining Tools & Wire Strainers



STRAINING TOOLS

Whites Rural offers a wide range of both temporary and permanent wire strainers. Proven designs that are hard wearing and built to last.

Chain Strainers

Removable tool for fence straining, the smooth grip jaws hold all common sizes of fence wire while minimising wire damage.

- Made in New Zealand
- Rugged steel handles, gold passivated finish
- 1.8 metre long chain

Fabricated Farm Fencing Strainers

Used with a chain strainer, it allows for easy straining and installation of fabricated farm fencing. 1.6m - ideal for exclusion fencing.

| Length | 1.2m | 1.6m |
|------------------|---------------|---------------|
| Clamping Points | 4 wedged pegs | 6 wedged pegs |
| Straining Points | 3 | 5 |

WIRE STRAINERS

Permanent Wire Strainers

The easy solution for fence erecting, wire alignment & fence maintenance fast and easy. Attach to fence line and tighten to strain. Permanent wire strainers stay on the fence line and can be re-tightened over time to prevent wire sag.

- Strainers made in New Zealand
- Galvanised steel
- Smooth ratchet action
- Standard and insulated available







| Code | Product | Weight |
|--------|--|--------|
| STRAIN | ING TOOLS | |
| 12102 | Contractor Chain Strainer | 3.8kg |
| 12105 | Contractor Fabricated Farm Fencing Strainer 1.2m | 9.1kg |
| 12097 | Contractor Fabricated Farm Fencing Strainer 1.6m | 13kg |
| 12109 | Replacement Wedge Pack (1.2m) | 0.65kg |
| | | |



| Code | Product | Pack Qty |
|-------|---|-------------|
| PERMA | NENT WIRE STRAINERS | |
| 12106 | Permanent Wire Strainer | 25 |
| 12500 | Insulated Perm. Wire Strainer - Plastic | 20 |
| 12501 | Insulated Perm. Wire Strainer - Porcelain | 20 |
| 12099 | Permanent Wire Strainer | 25 |
| 12090 | Permanent Wire Strainer - Bucket | 40 |









ST400i Impulse Fencing Staples & Fuel Cell Pack





ST315i Impulse Fencing Staples & Fuel Cell Pack

| Code | Product | Per Packet | Weight |
|-------|--|---------------|--------|
| STOCK | ade [®] IMPULSE [®] POWER STAPLING | | |
| 12440 | STOCKade ST315i Impulse Power Stapler | | 6.6kg |
| 12441 | STOCKade 33 x 3.15mm Impulse Barbed Staples | 2000 | 6.7kg |
| 12443 | STOCKade 40 x 3.15mm Impulse Staples | 1800 | 8.4kg |
| 12445 | STOCKade ST400i Impulse Power Stapler | | 4.2kg |
| 12446 | STOCKade 40 x 4.0mm Impulse Barbed Staples | 1000 | 7.75kg |
| 12448 | STOCKade 50 x 4.0mm Impulse Barbed Staples | 1000 | 10.2kg |
| STOCK | ade® IMPULSE® FENCING ACCESSORIES | | |
| 12439 | STOCKade ST315i Battery | | 0.09kg |
| 12449 | STOCKade ST400i Battery | | 0.09kg |

TOOLS

STAPLING Cordless Impulse Power

STOCKade[®] Impulse[®]

STOCKade Impulse power staplers combine faster fencing with hose-free portability in a gas cartridge gun.

ST400i Impulse Power Stapler

The ST400i has outstanding power allowing you to fire up to 650 staples per fuel cell and in conjunction with the 3.7V Li-ion battery, you can fire 3000 barbed, divergent point staples per charge per battery.

The ST400i kit also comes with 2 batteries so you will never run out of power.

- Impulse technology
- Ergonomic design
- Adjustable depth of drive
- Top load magazine
- V-notch guide and sequential trigger system



ST400i staples and fuel cell packs, each pack contains 2 fuel cells, enough for every staple in the pack. Available in 40mm & 50mm, with a 4mm wire diameter.

- Divergent point barbed fencing staple
- Zinc-Aluminium coating for longer life
- Superior driving and improved holding

ST315i Impulse Power Stapler

Driving 3.15mm staples at a rate of up to 2 staples per second, the unit is lightweight and comfortable and there is no need for an air compressor.

ST315i staples and fuel cell packs, each pack contains enough fuel for every staple in the pack. Available in 33mm & 40mm, with a 3.15mm wire diameter.







STOCKade[®] Pneumatic

The STOCKade pneumatic power stapler is designed for faster fencing and reduced manual effort.

The ST400 Pneumatic Power Stapler is engineered specifically for driving heavy-duty barbed fencing staples up to 50mm long.

- Dramatically increases stapling speed and productivity
- Aluminium alloy housing for extreme durability
- Adjustable power for high density timber

The world's only power-driven barbed staple for superior holding power.

- Available in 45mm & 50mm 4mm wire diameter
- Heavy Zinc-Aluminium Bezinal[®] 2000 coating
- Divergent point staples



| Code | Product | Per Packet | Weight |
|-------|---|---------------|--------|
| | ade [®] PNEUMATIC POWER STAPLING | rucket | reight |
| 12430 | STOCKade ST400 Power Stapler | | 6.6kg |
| 12454 | STOCKade 50 x 4.0mm Barbed Staples | 1000 | 10kg |

akes fencing Exclusively distributed in Australia by Whites Rural

FENCING STAPLES

Galvanised double pointed "U" nail for securing wire to timber frames and posts. Plain or barbed staples for added holding power.

- Galvanised for maximum durability
- Razor sharp points for fast, easy driving
- Suitable for securing wire, mesh and netting

Available in Hot-dipped galvanised for longer life.





| Code Product | Qty Per Packet | Weight | Carton Qty |
|------------------------------------|-------------------|--------|---------------|
| GALVANISED STAPLES | | | |
| 12503 50 x 4.0mm Barbed | 50 | 500g | 24 |
| 12509 40 x 4.0mm Barbed | 52 | 500g | 24 |
| 12513 30 x 4.0mm Barbed | 65 | 500g | 24 |
| 12416 25 x 3.15mm Plain | 132 | 500g | 24 |
| 12502 50 x 4.0mm Barbed | 300 | 3kg | 8 |
| 12506 40 x 4.0mm Barbed | 315 | 3kg | 8 |
| 12512 30 x 4.0mm Barbed | 390 | 3kg | 8 |
| 12412 25 x 3.15mm Plain | 795 | 3kg | 8 |
| 12517 50 x 4.0mm Barbed | 1500 | 15kg | 1 |
| 12518 40 x 4.0mm Barbed | 1600 | 15kg | 1 |
| HOT-DIPPED GALVANISED STAPLES | | | |
| 12504 50 x 4.0mm HDG Barbed | 500 | 5kg | 4 |
| 12510 40 x 4.0mm HDG Barbed | 575 | 5kg | 4 |
| 12505 50 x 4.0mm HDG Barbed | 1500 | 15kg | 1 |
| 12511 40 x 4.0mm HDG Barbed | 1600 | 15kg | 1 |









| | | Per | |
|-------|---|--------|--------|
| Code | Product | Packet | Weight |
| STOCK | ade [®] RINGFAST™ PNEUMATIC RING FASTENERS | | |
| 12308 | STOCKade RINGfast Pneumatic Tool (bonus case) | | 1.5kg |
| 12305 | STOCKade RINGfast Ring Fasteners | 1000 | 0.7kg |
| STOCK | ade [®] JAMBRO [®] RING FASTENERS | | |
| 12300 | Jambro Ring Fastener Gun | | 0.4kg |
| 12301 | Jambro Standard Ring Fasteners | 1000 | 1ka |



| Code | Product | Per Packet | Weight | Carton Qty |
|-------|---------------------|---------------|--------|---------------|
| WOOL | BALE FASTENERS | | | |
| 12330 | Wool Bale Fasteners | 100 | 500g | 24 |
| 12331 | Wool Bale Fasteners | 300 | 1.5kg | 8 |
| 12334 | Wool Bale Fasteners | 700 | 3.5kg | 4 |
| 12335 | Wool Bale Fasteners | | 15kg | 1 |
| | | | | |

TOOLS FASTENERS Pneumatic & Manual

STOCKade[®] RING*fast*[™]

The RINGfast pneumatic ring fastening tool quickly and consistently secures ring fasteners.

Faster than manual tools, reliable and relatively effortless, the pneumatic operation produces consistent rings fast, reducing manual effort and improving productivity.

The tool has been designed with an ergonomic grip and is balanced for comfortable operation.

- Quickly and consistently secures ring fasteners
- Reduces manual effort, improves productivity
- Ergonomic and comfortable to operate
- Zinc-Aluminium coating for longer life



JAMBRO[®] RING FASTENER

Whites Rural exclusively distributes the Jambro Ring Fastener Gun and Clips in Australia. Fast and reliable, this manual gun will fasten to a rate of 25 metres per minute.

The stainless steel jaws and precision body casting ensure quick and easy loading and firing. Use with Jambro high tensile ring clips.

- Faster fencing, 25 metres per minute
- Stainless steel jaws
- High tensile ring fasteners
- Zinc-Aluminium coating for longer life

WOOL BALE FASTENERS

Super sharp, galvanised and pressed cut to ensure the finest point. Penetrates fabric first time.

Designed to be used in conjunction with Australian Wool Exchange (AWEX) standards.

TOOLS

MaxTensor

Wire Joining, Tensioning & Terminating



MAX Engineering

Exclusively patented system, *MaxTensor's* all metal construction is designed for maximum quality, reliability and ease of use when joining and tensioning wire.

MAX Usability

Ergonomically designed for effortless practicality and long lasting performance, *MaxTensor* makes joining, straining and repairing fences easier.

MAX Reliability

With millions sold globally, *MaxTensor's* patented system is industry tested and proven against the best the world has to offer. Made in the EU to strict specifications.

Exclusively distributed throughout Australia & New Zealand by Whites Rural.



Barbed Wire - *MaxTensor* Medium Joiner & Tensioner will fit up to 1.57mm barbed wire.



High Tensile Wire - MaxTensor is specially designed for wire with a high breaking strain.



Electric Fencing - MaxTensor's all metal construction means there is no break in the current.



Zinc Aluminium - MaxTensor's cam wedge provides a strong grip to hold Zn Al coated wire.

All Metal Construction

Joiners & Terminators for fencing wire, horticultural wire & fabricated fence



MaxTensor is a complete range of joiners, tensioners, end post terminators and tensioning tools







12157

12159

12152



| Code | Product | Per Packet | Carton Qty | |
|---|---|---------------|---------------|--|
| MaxTen | sor® WIRE JOINERS & TENSIONERS | | | |
| 12157 | MaxTensor Medium Joiner - Blister Pack | 20 | 6 | |
| 12156 | MaxTensor Medium Joiner - Contractor Pack | 100 | 2 | |
| 12155 | MaxTensor Medium Joiner - Bulk Pack | 250 | - | |
| 12159 | MaxTensor Large Joiner - Blister Pack | 10 | 6 | |
| 12158 | MaxTensor Large Joiner - Bulk Pack | 150 | - | |
| MaxTensor® WIRE TERMINATORS & TENSIONERS | | | | |
| 12152 | MaxTensor Medium Terminator - Blister Pack | 10 | 6 | |
| 12151 | MaxTensor Medium Terminator - Bulk Pack | 300 | - | |
| MaxTensor® TENSIONING TOOLS (WITH 5 BONUS MEDIUM JOINERS) | | | | |
| 12160 | MaxTensor Polymer & Steel Core Tensioning Tool | | | |
| 12161 | MaxTensor Heavy Duty Steel Tensioning Tool - Contra | actor Grade | | |







| | | | | Carton |
|--------|--|-------|--------|--------|
| Code | Product | Size | Weight | Qty |
| PROFE | SSIONAL PLIERS & CUTTERS | | | |
| 12001 | Knipex Professional Wire Cutting Plier | 200mm | 0.4kg | 20 |
| 12041 | Toledo Pocket Bolt Cutter | - | 0.3kg | 60 |
| 12042 | Toledo Professional Parrot Beak Plier | 270mm | 0.7kg | 24 |
| 12043 | Toledo Professional Fencing Plier | 260mm | 0.5kg | 36 |
| 12044 | Toledo Professional Fencing Plier | 300mm | 0.8kg | 24 |
| FENCIN | IG PLIERS | | | |
| 12002 | Fencing Plier - Parrot Beak | 250mm | 0.6kg | 5 |
| 12003 | Fencing Plier - Bullnose | 250mm | 0.6kg | 5 |
| 12004 | Fencing Plier - Bullnose | 300mm | 0.7kg | 5 |



| Code | Product | Per Packet | Weight | Carton Qty |
|---------|------------------------------------|---------------|--------|---------------|
| FENCE | R'S TOOL | | | |
| 12005 | Fencer's Tool | - | 0.1kg | - |
| FENCE | POST CLIPS | | | |
| 12319 | Fence Post Clips (with tool) | 250 | 1.4kg | 8 |
| HEAVIL | Y GALVANISED PRE-CUT TIE WIRES | | | |
| 71541 | HG Pre-Cut Tie Wire 3.15mm x 300mm | approx 230 | 4kg | 3 |
| 71543 | HG Pre-Cut Tie Wire 2.50mm x 300mm | approx 340 | 4kg | 3 |
| HORSE | -SAFE POST CAPS | | | |
| 12348 | Horse-Safe Post Caps | - | 4.3kg | 40 |
| 12349 | Horse-Safe Post Caps XL | - | 3.2kg | 20 |
| FENCE | POST CAPS | | | |
| 12322 | Post Caps Yellow - 60mm | 40 | 0.8kg | 10 |
| STAY PI | NS | | | |
| 14340 | Stay Pins Galvanised 10 x 300mm | 50 | 9.5kg | |



| Code | Product | Length | Weight | Carton Qty |
|--------|-------------------------|--------|--------|---------------|
| FARM F | PAK™ TIE WIRES | | | |
| 50223 | 2.50mm Heavy Galvanised | 80m | 3kg | 5 |
| 50224 | 2.00mm Heavy Galvanised | 120m | 3kg | 5 |
| 50225 | 1.57mm Heavy Galvanised | 200m | 3kg | 5 |

TOOLS FFFSSOR Tools, Fencing & Tie Wire

FENCING PLIERS AND CUTTERS

Genuine Knipex® Quality

Knipex Professional Wire Cutting Plier made in Germany, from heat-treated Cr-V steel, with a tough cutting edge and a comfortable ergonomic design.

Genuine Toledo Pliers and Cutter

Durable and robust, designed for fencing. Made from chrome molybdenum steel and featuring specially heat-treated hardened jaws and cutting edges. Parrot-beak, bullnose and pocket cutter styles.

Fencing Pliers Also available Whites general purpose range fencing pliers.



FENCING ACCESSORIES

Fence Post Clips - Fixes plain or barbed wire to steel fence posts. Easy to use, each pack includes application tool.

Heavily Galvanised Pre-Cut Tie Wires Easy to work with low tensile, pre-cut 300mm lengths. A great time-saver alternative to cutting longer coils to suit. Heavily galvanised & supplied in re-usable handy packs.

Horse-Safe Fence Post Caps - Hi-visibility and UV-resistant featuring three-slot pattern to hold 5mm hot wire and/or 12-40mm electric tape. White colour for horse safety. Suit standard 'Y' or larger intermediate posts.

Standard Post Caps - Unique Fin Grip[™] system, snugly fits post with no need to tie down. With side holes for fence wire to pass through.

Stay Pins - Hot-dipped galvanised pre-cut 10mm rod lengths ideal for joining timber rails and posts. Long lasting, especially in CCA treated timbers. 300mm length for thicker timber and extra support.

Also available Whites pocket-sized fencing tool.

FARM PAK[™] TIE WIRES

Whites Rural Farm Pak Tie Wires are wound onto a 'no tangle' dispenser pack for ease of use. The 3kg packs are light enough to carry yet contain sufficient wire for most applications around the farm.

- Heavily Galvanised Wire
- 'No tangle' dispenser
 - Easy to handle 3kg packs
- Soft easy to tie

34



Posts · Fencing · Gates · Tools

Expect More

The market has learnt to expect more from Whites Rural for products and service built around down-to-earth Australian family values.

Our long history of continuous improvement has yielded many new and unique product offerings, always striving to provide greater value to farmers and fencing contractors in the rural market.

Since the launch of Stockpost in 2012, featuring market leading strength, Whites Rural have continued to bring greater value to the Australian market with the introduction of the Australian designed Ute Pack, followed by the ground breaking Stockpost XL and End Assembly ranges.

Whites Rural's recent acquisition of Australia's only regionally-based rural wire fencing manufacturer has strengthened its connection to rural Australia. This long-term commitment ensures Whites Rural is well poised to deliver more, so you can Expect More.

www.whitesrural.com.au











Pemulwuy, NSW 2145

SYDNEY

5 Dolerite Way

Whites Group Pty Ltd

ABN 25 001 845 478

BRISBANE Unit 4, 15 Seeana Place Heathwood, QLD 4110 MELBOURNE 64 Colemans Road Dandenong South, VIC 3175 TOWNSVILLE 13 Crocodile Crescent Mt St John, QLD 4818

PERTH 53 Collopy Road Perth Airport, WA 6105 ADELAIDE 18 Bradford Way Cavan, SA 5094

Enquiries: 1300 559 732 Fax: 1300 559 762 Email: info@whitesrural.com.au Specifications referred to in this publication are subject to change, variation and/or improvement without notice.

For the most up-to-date details on all our rural products, visit our website at www.**whitesrural**.com.au



88934 - 06/2020